



MXP/MXA series

Fixed displacement hydraulic motors

The MXP/MXA motors deliver reliable and efficient performance for intermittent duty applications in truck equipment.

Technical data

Motor model	Displacement (cc/rev)	Maximum continuous speed (rpm)	Maximum intermittent speed (rpm)	Maximum flow absorbed (L/min)	Torque per bar (N·m/bar)	Torque at 350 bar (N·m)	Minimum / maximum motor temperature (°C)*	Maximum allowable pressure (continuous / peak) (bar)
MXP12	12	8000	8800	96	0,19	66	−25 / 110	400 / 450
MXP18	18	8000	8800	144	0,28	98	−25 / 110	400 / 450
MXP25	25	6300	6900	158	0,4	140	−25 / 110	400 / 450
MXP32	32	6300	6900	202	0,5	175	−25 / 110	400 / 450
MXP41	41	5600	6200	230	0,65	227	−25 / 110	400 / 450
MXP50	50,3	5000	5500	252	0,8	280	−25 / 110	400 / 450
MXP63	63	5000	5500	315	1	350	−25 / 110	400 / 450
MXP80	80,4	4500	5000	362	1,27	445	−25 / 110	400 / 450
MXP90	90	4500	5000	405	1.43	501	−25 / 110	400 / 450
MXP108	108,3	4000	4400	435	1,7	595	−25 / 110	400 / 450
MXP126	126	3400	4400	428	2,0	700	−25 / 110	400 / 450



Product catalogue
➤ Open



Product webpage
➤ Open