

XR SERIES

Fixed displacement pumps

The XR pump range combines advanced design, high self-priming capability, and robust construction, ensuring efficient and reliable performance in the most demanding truck applications.



Technical data

Pump reference	Direction of rotation	Displacement	Max. continuous pressure	Max. peak pressure < 5 seconds	Max. speed ⁽¹⁾	Theoretical torque at Max. continuous pressure	Weight		Overhang torque	
		(cc/rev)	(bar)	(bar)	(rpm)	(N.m)	Without inlet fitting	With inlet fitting 2''	Without inlet fitting	With inlet fitting 2''
XR63	Right (CW)	63,1	400	450	2350	401,1	11,4	11,98	11,97	12,77
	Left (CCW)									
XR80	Right (CW)	80,4	400	450	2350	511,5	14,89	15,47	17,21	18,73
	Left (CCW)									
XR108	Right (CW)	108,3	400	450	2000	689,1	15,16	15,74	17,88	19,07
	Left (CCW)									
XR130	Right (CW)	129,9	400	450	2000	826,2	15,39	15,97	18,01	19,55
	Left (CCW)									

(1) At absolute pressure 1 bar, ISO VG46 fluid at 25°C.



Product catalogue

➤ Open



Product webpage

➤ Open